



ISO 9001:2008
ISO 14001:2004



Containers with side door

P.P.H. AMG Sp. z o.o.
ul. Słupska 18; 84-300 Lębork; Poland
Tel. +48 59 862 32 77, Fax +48 59 862 23 15, e-mail: office@amg.pl

www.amg.pl



ISO 9001:2008
ISO 14001:2004

Area of use:

Intended for collection and transportation of waste electrical and electronic equipment, baled secondary raw materials, pallets, cargo and hazardous waste, as well as other goods which could be loaded/unloaded with a forklift from the side. Could be used as storage container.

Technical specification:

- the capacity of the container is 35- 46 m³,
- frame according to SS, DIN and other standards,
- hook lift loading system,
- double door with a door locking and security blocking fitted on the side of the container,
- version with side doors
- medium Version: thickness of steel sheets bottom: 4mm; walls: 3mm, Frame span: 750mm
- heavy Version: thickness of steel sheets bottom: 5mm; walls: 4mm, Frame span: 750mm
- with side doors
- "Hardox/ Domex" version or Hardox/ Hardox steel sheets

Special Options:

- single door fitted with a security locking on the side of the container, top hinged rear door, also fitted with a rubber seal,
- mounted on an extended section or at level with the base of the container,
- logo plate
- roller cover,
- permanent roof,
- sliding roof slideable by hand,
- lifting roof lifted by a lifting break or a hydraulic pump,
- the forklift pockets under the containers

Our company also produces:

- Hooklift containers complies with the requirements of SS-3021 standards or with the customers guideline, the capacity of the container is 10 - 49 m³
- Type "Open Lift", built according to SS-3020 standards with a capacity of 1 - 12 m³, while the thickness of the metal used varies according to the order.
- Type "Combo", built according to DIN 30720 standards with a capacity between 2,5 - 12 m³ while the thickness varies according to the demands of the client. The lids on these bins are equipped, however if the customer so pleases in steel, aluminum and PCV lids can be added.
- a wide variety of containers built in accordance to German standards DIN30720 and DIN3072-1
- Storage container the length of 8 to 10 feet, adapted for vehicle transport or fork lifts and equipped with anti - leak double wing doors which ensure that no water will leak into the container
- Oil reservoirs according to clients demands.



P.P.H. AMG Sp. z o.o.
ul. Słupska 18; 84-300 Lębork; Poland
Tel. +48 59 862 32 77, Fax +48 59 862 23 15, e-mail: office@amg.pl

www.amg.pl